

Numatic H-Class Range

HZC390L/S (H Class)



Data Sheet

Rated Motor Power (W)	1000 W
Power	230v AC 50/60Hz
Airflow Motor only	48 L/sec
Max Suction H ² O	2500
Kit	AA16
Capacity (DRY)	13.0 Litres
Cleaning Range (M)	26.8
Weight (Ready to use)	12.2 / 13.0 kg
Dimensions (W x L x H) Long Handle	400mm x 450mm x 1010mm
Dimensions (W x L x H) Short Handle	400mm x 450mm x 600mm
Mains Lead	HO5VV-F 10 x 3 x 1.00 mm ²
Protection Class	Class I
HZC Disposable Cartridge	909007 to Re-order Replacement
Dust Hazard Class	H
Filtration Efficiency Class	H13 (EN1822)

Designed, engineered and built with the tradesman in mind, the HZC390 offers a safe and convenient solution for those whose work brings them into frequent contact with hazardous dusts and materials.

Equipped with a sealed and disposable HEPA H13 filter cartridge, all dust is safely contained, meaning users can change the filter as and when they need to.

**H-Class Compliant
Unparalleled Safety
Compact & Ready
Take Control
All-Terrain**

DRY

UNITED KINGDOM: www.numatic.co.uk

NETHERLANDS: www.numatic.nl

PORTUGAL: www.numatic.pt

GERMANY: www.numatic.de

SWITZERLAND: www.numatic.ch

SPAIN: www.numatic.es

FRANCE: www.numatic.fr

SOUTH AFRICA: www.numatic.co.za

Specification subject to change without prior notice
www.numatic.co.uk © Numatic International Limited